

In the claims:

The claims currently in the application are set forth below. Claims 1-16 and 21-25 have been previously cancelled. New claims 26-46 have been added herein. A complete set of claims, as currently amended, is provided below.

Claims 1-16 (previously canceled)

---

17. (previously presented) A method for replacing a first printhead operably secured to a carriage of an inkjet printer with a second printhead, the inkjet printer having an on-axis ink reservoir pivotally secured to the carriage defining a secured position of the ink reservoir with respect to the ink reservoir mounting-portion and defining an engaged position in which the ink reservoir is in fluid communication with the printhead, said method including the steps of:

locating the carriage containing the first printhead;

pivoting the ink reservoir out of its engaged position such that the first printhead is exposed and easily accessible in the carriage while maintaining said ink reservoir in said secured position, and thereby automatically disconnecting the fluid communication between the ink reservoir and the first printhead and providing access to said first printhead without removing said ink reservoir from said secured position;

removing the first printhead from the carriage while maintaining the ink reservoir in said secured position;

installing the second printhead in the carriage such that the second printhead is operably secured to the carriage while maintaining the ink reservoir in said secured position; and,

returning the ink reservoir to its engaged position thereby automatically placing the ink reservoir and second printhead in fluid communication with each other without removing said ink reservoir from said carriage.

18. (original) The method for replacing a first printhead operably secured to a carriage of an inkjet printer with a second printhead of claim 17, wherein said locating the first printhead step includes positioning the carriage in the printer such that it is easily accessible through an access door on the printer.

19. (original) The method for replacing a first printhead operably secured to a carriage of an inkjet printer with a second printhead of claim 17, wherein said first and second printheads are detachably secured to said carriage.

20. (original) The method for replacing a first printhead operably secured to a carriage of an inkjet printer with a second printhead of claim 17, further including the steps of:

unlatching a latching mechanism extending between structures containing the ink reservoir and first printhead to initiate said step of pivoting the ink reservoir out of its engaged position; and

latching the latching mechanism following said step of returning the ink reservoir to its engaged position.

Claims 21-25 (previously canceled).

26. (new) A carriage for an inkjet printer comprising:

a printhead mounting portion;

a printhead operably secured to said mounting portion;

an ink reservoir mounting portion pivotally secured to said printhead mounting portion;

an ink reservoir operably secured to said ink reservoir mounting portion to define a secured position in which said ink reservoir is secured to said ink reservoir mounting portion;

said ink reservoir having an engaged position in which the ink reservoir is in fluid communication with said printhead when said ink reservoir is in said secured position, and an open position, in which the ink reservoir mounting portion is pivoted away from said printhead mounting portion such that said printhead may be accessed from above said printhead mounting portion without removing said ink reservoir from said secured position on said ink reservoir mounting portion.

27. (new) The carriage for an inkjet printer of claim 26, further including:  
a plurality of ink reservoirs; and  
a plurality of printheads;  
wherein one of each plurality of ink reservoirs is in fluid communication with a  
respective one of each plurality of printheads in said engaged position.

28. (new) The carriage for an inkjet printer of claim 26, further including a  
channel extending between said ink reservoir and said printhead in said engaged  
position.

29. (new) The carriage for an inkjet printer of claim 28, wherein said  
channel is substantially air tight when said carriage is in said engaged position such  
that a vacuum formed in the channel will cause ink to flow, and said channel is not  
substantially air tight when the carriage is moved out of its engaged position, thereby  
preventing ink from flowing through the channel.

30. (new) The carriage for an inkjet printer of claim 26, wherein said  
printhead mounting portion is pivotally secured to said ink reservoir mounting portion  
at a pivot point.

31. (new) The carriage for an inkjet printer of claim 30, wherein said  
printhead is detachably secured to said printhead mounting-portion.

32. (new) The carriage for an inkjet printer of claim 31, wherein said ink  
reservoir is detachably secured to said ink reservoir mounting-portion.

33. (new) The carriage for an inkjet printer of claim 30, further including:  
a resistive detent on one of said printhead mounting-portion and said ink  
reservoir mounting-portion; and,  
a tab extending from the other of said printhead mounting-portion and said ink  
reservoir mounting-portion for operably engaging said resistive detent when said ink

reservoir is in said open position, thereby holding the ink reservoir in said open position to further facilitate removal of the printhead.

34. (new) The carriage for an inkjet printer of claim 30, further including a shaft extending from one of said printhead mounting-portion and said ink reservoir mounting-portion, said shaft having a mating end portion; and

a mating hole for receiving said shaft in the other of said printhead mounting-portion and said ink reservoir mounting-portion, said mating hole including a notch for operably receiving said mating end portion of said shaft only when said ink reservoir is in said engaged position.

35. (new) The carriage for an inkjet printer of claim 30, further including a latching mechanism for detachably securing said printhead mounting portion to said ink reservoir mounting-portion thereby holding said ink reservoir in said engaged position.

36. (new) The carriage for an inkjet printer of claim 35, wherein said latching mechanism includes:

a handle pivotally secured to one of said printhead mounting-portion and said ink reservoir mounting-portion at a pivot;

a joining arm extending from said handle; and

a hook for receiving said joining arm extending from the other of said printhead mounting-portion and said ink reservoir mounting-portion such that said hook operably engages said joining arm when said handle is pivoted about said pivot.

37. (new) An inkjet printer comprising:

a chassis;

a motor;

a carriage operably secured to the chassis and driven by the motor for reciprocal movement relative to the chassis;

a printhead operably secured to said carriage;

an ink reservoir operably secured to said carriage in a secured position such that said ink reservoir may pivot about said printhead at a pivot point while remaining in said secured position, said carriage having an engaged position in which the ink reservoir is in fluid communication with said printhead when said ink reservoir is in said secured position, and an open position, in which the ink reservoir is pivoted about said pivot point away from said printhead, such that said printhead may be accessed from above said carriage without removing said ink reservoir from said secured position.

FI 38. (new) The inkjet printer of claim 37, further including a channel extending between said ink reservoir to said printhead when said carriage is in said engaged position.

39. (new) The inkjet printer of claim 38, wherein said channel is substantially air tight when said carriage is in said engaged position such that a vacuum formed in the channel will cause ink to flow, and said channel is not substantially air tight when the carriage is moved out of its engaged position, thereby preventing ink from flowing through the channel.

40. (new) The inkjet printer of claim 37, wherein said printhead is operably secured to said carriage at a printhead mounting-portion, and said ink reservoir is operably secured to said carriage at an ink reservoir mounting-portion; and wherein said printhead mounting-portion is pivotally secured to said ink reservoir mounting-portion at said pivot point.

41. (new) The inkjet printer of claim 37, further including:  
a second ink reservoir operably secured to said carriage; and,  
a second printhead operably secured to said carriage,  
wherein said first ink reservoir includes black ink, and said second ink reservoir includes a plurality of chambers for receiving a plurality of different colored

inks.

42. (new) A carriage for an inkjet printer comprising:  
a first mounting portion;  
a printhead operably secured to said first mounting portion;  
a second mounting portion operably secured to said first mounting portion  
such that said second mounting portion moves toward and away from said first  
mounting portion along a defined path;  
an ink reservoir operably secured to said second mounting portion in a  
secured position,  
said second mounting portion having an engaged position in which the ink  
reservoir is in fluid communication with said printhead when said ink reservoir is in  
said secured position, and an open position in which the second mounting portion is  
moved away from the first mounting portion along the defined path and said ink  
reservoir remains in said secured position thereby providing access to the printhead  
without detaching said ink reservoir from said secured position on said second  
mounting portion.

43. (new) The carriage for an inkjet printer of claim 42, wherein said first  
mounting portion is pivotally secured to said second mounting portion at a pivot  
point.

44. (new) The carriage for an inkjet printer of claim 42, wherein said first  
mounting portion is a printhead mounting-portion and said second mounting portion  
is an ink reservoir mounting-portion.

45. (new) The carriage for an inkjet printer of claim 44, wherein said  
printhead is detachably secured to said printhead mounting-portion.

46. (new) The carriage for an inkjet printer of claim 45, wherein said ink  
reservoir is detachably secured to said ink reservoir mounting-portion.